



項目	仕様	納入品目	記
3.0	仕様		
3.1	チャック形番	H3KS15	1台
3.2	シリンダ形番		
3.3	プランジャストローク	35 mm	標準付属品・工具
3.4	ジョーのストローク (直径)	最大 16 mm	
3.5		常用	
3.6	使用油圧力	最大	
3.7		常用	
3.8	許容シリンダ力	82 kN	
3.9	把握力 (許容シリンダ力時)	249 kN	
4.0	把握トルク ()		
4.1	最高使用回転数	3040 r/min	
4.2	質量	100 kg	
4.3	慣性モーメント	1.88 kg·m ²	
4.4			
4.5			
4.6			
4.7			
4.8			
4.9			
4.10			
4.11			
4.12			
4.13			
4.14			
4.15			
4.16			
4.17			
4.18			
4.19			
4.20			
4.21			
4.22			
4.23			
4.24			
4.25			
4.26			
4.27			
4.28			
4.29			
4.30			
4.31			
4.32			
4.33			
4.34			
4.35			
4.36			
4.37			
4.38			
4.39			
4.40			
4.41			
4.42			
4.43			
4.44			
4.45			
4.46			
4.47			
4.48			
4.49			
4.50			
4.51			
4.52			
4.53			
4.54			
4.55			
4.56			
4.57			
4.58			
4.59			
4.60			
4.61			
4.62			
4.63			
4.64			
4.65			
4.66			
4.67			
4.68			
4.69			
4.70			
4.71			
4.72			
4.73			
4.74			
4.75			
4.76			
4.77			
4.78			
4.79			
4.80			
4.81			
4.82			
4.83			
4.84			
4.85			
4.86			
4.87			
4.88			
4.89			
4.90			
4.91			
4.92			
4.93			
4.94			
4.95			
4.96			
4.97			
4.98			
4.99			
5.00			

納入先	○計画図 ○見積図	◎納入仕様図 ○製作図
尺 1:1	SCALE 1:1	H3KS15
APPROVED	CHECKED	DESIGNED
名称 TITLE 楔形3爪セレーテッドチャック		
図番 DRAWING NO. B-520		
豊和工業株式会社 HOWA MACHINERY, LTD.		