



図面記号	仕様	納入品目	記
01	チャック形番 H064M8	H064M8	1台
02	シリンダ形番		
03	プランジャストローク	14.4 mm	標準付属品・工具
04	X2におけるジョーのストローク(直径)	最大 9.2 mm 常用	1式
05	使用油圧力	最大 MPa 常用	
06	許容シリンダ力	18.9 kN	
07	把握力(許容シリンダ力)	32.7 kN	
08	把握トルク	0.12 kg·m ²	
09	最高使用回転数	3000 r/min	
10	質量(標準生爪を含む)	26.5 kg	
11	慣性モーメント		
12	把握範囲	外径 16~150 mm 内径 7.6~203 mm	
13			
14			
15			
16			
17			
18			
19			
20			
21			
22			
23			
24			
25			
26			
27			
28			
29			
30			
31			
32			
33			
34			
35			
36			
37			
38			
39			
40			
41			
42			
43			
44			
45			
46			
47			
48			
49			
50			
51			
52			
53			
54			
55			
56			
57			
58			
59			
60			
61			
62			
63			
64			
65			
66			
67			
68			
69			
70			
71			
72			
73			
74			
75			
76			
77			
78			
79			
80			
81			
82			
83			
84			
85			
86			
87			
88			
89			
90			
91			
92			
93			
94			
95			
96			
97			
98			
99			
100			

納入先

尺 1:1
SCALE 1:1

APPROVED CHECKED DESIGNED

名称 TITLE H064M8

2爪スイングロックチャック

製 豊和工業株式会社
HOWA MACHINERY, LTD.

図番 DRAWING NO. B-228H